

~~Description~~

This is a U.S. national phase application under 35 U.S.C. §371 of International Patent Application No. PCT/EP2005/003142, filed March 24, 2005, and claims benefit of German Patent Application No. 10 2004 015 78.8, filed March 25 2004 which is incorporated by reference herein. The International Application was published in German on October 6, 2005 as WO 2005/093149 A1 under PCT Article 21(2).

BACKGROUND

[0004] Document DE 41 00 767 A1 discloses an annular illumination device for a household appliance, said annular illumination device being designed as an optical waveguide and used, for example, as a visual edge boundary for cooktops or rotary selector switches.

[0005] In Document DE 196 49 039 C1 describes a drum-type washing machine having an illumination device whose light source is located in the area of the door hinge, and in which the light input and light output surfaces of an optical waveguide are arranged in a manner allowing the interior of the laundry drum and the area in front of the loading opening to be illuminated when the door is closed and when it is open.

[0006] The light source of that illumination device is mounted in the area of the door hinge and connected to the light-emitting means via a light-conductive connection. The door glass of the door is used as the light-emitting means, said door glass being in light-conductive connection with the light source via optical waveguides. This arrangement illuminates the interior of the drum. The loading opening and the space in front of the loading opening are illuminated when the door is in the open position.

[0007] Document DE 42 20 018 A1 discloses an illumination device for a laundry appliance, where the light source is disposed in the filling ring outside the sealing area of the suds container, and in such a manner that it is accessible from outside the appliance when the door is open. In this design, the edge of the drum acts as a reflector and the door glass provides assistance as an optical waveguide. When the door is open, the area in front of the appliance is also illuminated.

[0008] In order to illuminate the area in front of the appliance, it is known from US Patent No. 3,220,229 to mount an illumination device above the loading opening of the drum, said illumination device illuminating the area in front of the appliance when the door is closed. The lamp is disposed behind a hinged service cover for the condensation device, said service cover having a glass panel to illuminate the area in front of the appliance.

SUMMARY

[0009] The An object of the present invention is to ~~design-provide~~ a laundry appliance having an illumination device in a manner that allows for glare-free illumination of the edge area of the door both in appliances with a door glass and in appliances that do not have a door glass.

~~[0010] This object is achieved in accordance with the present invention by an illumination device having the features of Claim 1. Advantageous embodiments and refinements of the present invention will become apparent from the following dependent claims.~~

[0010.1] The present invention provides a laundry appliance. The laundry appliance includes a housing including a stamped section recessed relative to a front of the housing and circumferentially surrounding a loading opening for a rotatably mounted drum of the appliance. A door is disposed on the front of the housing for closing the loading opening, an edge of the door and a surrounding edge of the stamped section forming a gap area therebetween when the door is in a closed position. An illumination device is disposed in the stamped section so as to be concealed behind the door when the door is in the closed position, light of the illumination device being reflected at an edge surface of the stamped section and a surface of the door edge so as to provide an illuminating ring visible at the front of the housing in the gap area.

~~[0011] One particular advantage that can be achieved with the present invention is provided by the illumination device which is arranged such that it is concealed behind the edge of the door and produces an illuminating ring in the gap area between the door and the housing by light reflection at the edge surfaces of the stamped section in the housing front and at the door edge. Due to the concealed arrangement of the illumination device, the illuminating ring becomes visible at the front of the housing without producing glare. The illumination device can be similarly arranged in laundry machines having a door of closed design which does not have a door glass.~~

BRIEF DESCRIPTION OF THE DRAWINGS

~~[0012] An exemplary embodiment~~ Exemplary embodiments of the present invention ~~is~~ are shown in the drawings in a ~~purely~~ schematic way and will be described in more detail below. In the drawings,

[0013] FIG. 1 is a view showing illumination device (7) of the laundry appliance along with an optical waveguide (9);

[0014] FIG. 2 is a cross-sectional side view taken along line A-A, showing the area of loading opening (2) and including a schematic representation of illumination device (7) with door (3) in the closed position; and

[0018] Edge surface (11), which surrounds stop surface (10) of the stamped section, is shaped as a truncated cone. In the closed position, door (3) is received in the stamped section in housing front (1) approximately flush therewith. Retaining ring (5) for door glass (4) is provided on the front with an annular cover (12) which, when door (3) is closed, partially covers the annular gap (13) that exists between retaining ring (5) and edge surface (11) surrounding circular stop surface (10) and which has the dimension X (gap area).

[0019] The light of concealed illumination device (7) is reflected at edge surfaces (11) of the stamped section and at stop surface (10). Thus, annular gap (13) is uniformly illuminated, so that an illuminating ring becomes visible toward housing front (1).

[0020] FIGS. 3a and 3b are schematic cross-sectional side views of a stamped section (9, 10, 11) having a truncated-cone-shaped edge surface (11), in which are received and integrated illumination device (7) including optical waveguide (9). Shaded area (14) is intended to symbolize the adjacent drum of the laundry appliance.

[0021] In another exemplary embodiment (not shown), the light source FIG. 3c is a schematic cross-sectional side view of a stamped section (10, 11) having a truncated-cone-shaped edge surface (11), in which are received and another embodiment of integrated illumination device (7). In this embodiment, the illumination device (7) is in the form of LEDs (15) which are arranged circumferentially around the loading opening in stamped section (10, 11) and backlight a diffuser or a diffusing screen (16).

[0022] The above-described variants of the illumination devices make it possible to indicate different operating states of the appliance. The light sources can, for example, be driven such that, for example, blinking white light symbolizes the program start. Moreover, it is possible to additionally provide colored light sources which can be used to indicate malfunctions (red light) or the end of the program (green light), when driven accordingly. The illumination device can be similarly arranged in laundry machines having a door of closed design which does not have a door glass.

[0022.1] The present invention is not limited to the exemplary embodiments described herein; reference should be had to the appended claims.